Electric Radiator 0.6, 0.9, 1.5 and 1.8 kW



p.100

Usage


A stylish, modern fixed heating solution that is suitable for application in both home and office environments and features a slimline, curved design.

Features and Benefits

- Slimline, modern, curved design
- Available in 0.6, 0.9, 1.5 and 1.8 kW
- · Ecodesign compliant
- High precision digital thermostat accurate to the nearest degree
- 24/7 LCD timer
- 2 user set temperature settings: peak for whilst the room is occupied and off peak (typically night or frost protection)
- Adjustable temperature range 10 - 35°C
- Open window detection to reduce energy wastage

- Ceramic heating element and dry thermal technology
- · Radiant and convection heat
- Choose from pre-set schedules or create your own to meet specific lifestyle requirements
- · Thermal safety protection
- Frost protection function set at 7°C
- Wall mounted secure bracket included
- · Integrated child lock
- White finish

Product Code	Power (kW)	Timer	Current (amps)	Number of Fins
AVG600T	0.6	Yes	2.6	4
AVG900T	0.9	Yes	4.4	5
AVG1500T	1.5	Yes	6.5	9
AVG1800T	1.8	Yes	8.7	10



Outer Casing Die cast aluminium

Die cast aluminium

Digital LCD display, controls and screen.

Overheat temperature protection.

IP Rating

IP20

Installation

Wall mounting kit included and must be used.

Electrical Connection Installation must comply with current IEE regulations.

The product should be connected to the fixed wiring of the property via a double pole fused spur with a minimum break capacity of 13 amps.

Cable pre-wired (1.4m), white cable, entry to the bottom right of the unit.

Class I

Approvals CE

Standard Warranty 1 year parts or replacement

warranty.

Product Code	Height (mm)	Width (mm)	Depth (mm)	Weight (kg)
AVG600T	575	480	80	8.5
AVG900T	575	560	80	10
AVG1500T	575	880	80	15.5
AVG1800T	575	960	80	19