

## Taps

### Non-Concussive, Single Lever Mixer Automatic Infrared



#### Usage

This range of taps is ideal for use with Hyco Rho and Aquila instantaneous water heaters to provide optimum hand washing performance in washroom settings and for use with Hyco Speedflow and Powerflow unvented water heaters.




#### Features and Benefits

- Sprayhead range of taps all with removable M22/ M24 nozzles
- Reduce water consumption by up to 50% compared to traditional taps by controlling the flow rate
- Save energy by up to 50% compared to traditional taps by reducing the amount of hot water required per hand wash
- Where the taps are used with a Speedflow or Powerflow water heater an optional thermostatic mixing valve is recommended (see page 50)
- Rho and Aquila instantaneous water heaters are only intended for use with spray head taps of this type. If traditional taps which do not control the water flow rate are used then optimum performance will not be achieved.
- All taps supplied complete with a choice of tap spray nozzles
- Other flow rates available on request

Product Code	Description	Reach (mm)
TAPNC	Non-concussive tap	110
TAPSLM	Single lever mixer tap	95
TAPIFR	Automatic touch free tap	110

#### Tap Spray Nozzle Options

Product Code	Max Flow Rate (l/m)	Best suited to water heater	Colour Code Identification
IN-TSN-2.5	2.5	4.4, 6.0 kW Rho	White/Green
IN-TSN-3.0	3.0	9.6 kW Aquila	White/Lilac



**Non-Concussive Tap**

Simple 'push tap' operation. Tap functions for a period of time and then closes automatically. Prevents vandalism and continuous running and saves water. Use for hot or cold water – blue and red identification rings supplied with each tap. WRAS approved.



**Single Lever Mixer Tap**

Simple manual operation by lifting the control lever up and down. Rotating the control lever clockwise or anti-clockwise reduces or increases the mixed water temperature.



**Automatic Infrared (Touch Free) Tap**

Hygienic no touch automatic operation. Dual mains or battery powered operation. Complete with cable for connection to the power supply. Usage timer prevents vandalism and continuous running and saves water. Mixer lever gives option to dispense hot and cold water if required. WRAS approved.



**Standard Warranty**

1 year parts or replacement warranty for all tap models.

Product Code	Height (mm)	Diameter (mm)	Width (mm)	Weight (kg)
TAPNC	140	50	150	0.8
TAPSLM	160	50	160	1
TAPIFR	140	50	150	1.7