

Zen Life 100°C

Boiling Water Tap with Kitchen Hot and Cold Mixer 3 and 6 litre boiling water tank



The elegant 3 in 1 tap provides instant true boiling 100°C water alongside hot and cold mixer tap capabilities.

It is perfect for retro-fit applications as well as new kitchens. This is the only tap you need in your kitchen.

Usage



The Zen Life is a practical and stylish choice when considering any commercial or domestic kitchen.

Features and Benefits

- Creates a clutter free and simplified design within any kitchen or office
- Instant true boiling 100°C water ideal for a wide range of kitchen uses
- Designed and assembled in the UK
- Time and space saving
- Suitable for commercial or domestic applications
- Energy efficient - standing loss only 17 W for 3L boiling tank and 20 W for 6L model
- High flow rate over 3 l/m and high initial capacity makes it quick and easy to use.
- Safety lock on the boiling side
- Innovative aerogel insulation on boiling tank minimises losses
- Boiling water tank has smart technology algorithms that learn and predict usage
- Cool touch insulated tap with 360° swivel function
- Zen Life tap should be mounted over a sink. Not suitable for use with a Zen font and drain.
- Boiling water status ring on base of tap to indicate ready or heating (green/ red LED)
- Dispensed water temperature can be adjusted down to 98°C on installation if required
- Available with 3 or 6L boiling water tank
- Power rating 1.60 kW for 3L and 2.84 kW for 6L model
- Standard sink hot and cold mixer supplied from your existing hot and cold mains water supply
- Consider installing a Speedflow to provide hot water for dish washing if there is no central heating system nearby (page 40)
- Must be fitted with initial scale filter (F5SST) supplied for inlet to boiling tank (see specification on page 32)
- Elongated mixer lever for ease of use total length 100 mm length from centre 80 mm
- Shorter mixer lever for restricted space kitchens total length 70 mm length from centre 55 mm
- Recovery Rate 90 cups/ 60 mugs per hour for 3L model and 160 cups/ 107 mugs per hour for 6L model based on 167 ml cup and 250 ml mug.

p.20

Product Code	Capacity (litres)	Heat Up Time (mins)	Standing Loss (kWh/day)
LIFE3L	3	12	0.42 17 W
LIFE6L	6	14	0.50 20 W



Outer Casing

Tap – polished chrome finish as standard
Other tap finishes available at additional cost (page 13)
Tank – durable high impact PC/ ABS

Water Tank

High quality grade 316L stainless steel

Heating Element

Incoloy

Thermostat

Electronic to control water up to boiling point

Insulation

Highly efficient aerogel thermal insulation

Initial Draw off

3L model - 18 cups/ 12 mugs
6L model - 36 cups/ 24 mugs
based on 167 ml cup/ 250 ml mug.

Safety

Overheat temperature protection (manual re-set).

Safety lock mechanism.

Supplied expansion vessel and pressure relief valve must be fitted.

IP Rating

IPX1

Installation

This appliance must be installed in a frost free environment

Required hole diameter for mounting tap 32mm – fits in a standard sink.
Sink/ counter top up to 50mm thick.

Plumbing

Must be installed by a suitably qualified person.

Intended for connection to the mains water supply.

Minimum water pressure 1 bar.

Maximum water pressure 4.2 bar. If higher than this a pressure reducing valve is required.

Supplied filter, expansion vessel and pressure relief valve must be fitted.

Electrical Connection

Installation must comply with current IET wiring regulations.

Supplied with a pre-wired (1m) BS plug.

Approvals

CE, UKCA

Standard Warranty

2 years parts or replacement warranty. Supplied scale filter must be fitted and changed at least every 6 months otherwise the warranty may be void.

Product Code	Height (mm)	Width (mm)	Depth (mm)	Weight (kg)	
				Empty	Full
ZEN Life Tap	365	286	56	2.5	–
ZEN Tank 3L	460	182	221	5.8	8.8
ZEN Tank 6L	460	220	270	6.7	12.7