

Zen Spa 100°C

2 in 1 Boiling and Chilled Tap
3 and 6 litre boiling water tank



In the home it replaces the need for a kettle and provides high quality cold drinking water.

In the office it replaces the traditional need for a wall mounted boiling water unit and separate floor standing chiller.

Usage

The Zen Spa is a 2 in 1 hot and cold drinks station.

The Zen Spa can be installed over a sink or with a stylish, tempered glass design Zen Font.

Features and Benefits



- All of the features and benefits of the Zen Solo plus cold (ambient) or chilled drinking water from a single tap
- Commercial specification available in 3 and 6L models
- Energy efficient boiling water tank - costs just 4 p a day, based on standing losses 17 W. Electricity cost 10 p/ kWh.
- High flow rate over 3 l/m and high initial capacity of 11 mugs makes it quick and easy to use.
- Modular solution allows you to tailor the tap to your individual requirements
- Cold (ambient) drinking water models connect directly to the incoming water supply
- Chilled drinking water models include a Sapphire undersink chiller (page 26)
- Dispensed water temperature can be adjusted down to 98°C on installation if required
- Must be fitted with initial scale filter (F5SST) supplied for inlet to boiling tank and cold drinking water filter (see specification on page 34 - 35)
- Available in 3 or 6L. 6L model comprises 2 x 3 litre boiling water tanks with linking kit.
- 6 litre tank 2.84 kW coming soon
- Recovery Rate 100 cups/ 70 mugs per hour based on 167 ml cup and 250 ml mug
- Double recovery rate for 6 litre model

Zen Spa Options

Product Code	Description
SPA3L	Zen Spa 100°C Tap 3L Boiling and Ambient
SPA6L	Zen Spa 100°C Tap 6L Boiling and Ambient
SPA3LUC1	Zen Spa 100°C Tap 3L Boiling and 20 l/h Chilled
SPA6LUC1	Zen Spa 100°C Tap 6L Boiling and 20 l/h Chilled

Product Code	Capacity (litres)	Heat Up Time (mins)	Standing Loss (kWh/day)*
SPA3L	3	13	0.42 17 W
SPA6L	6	13	0.84 34 W

* Standing loss figures are for the boiling tank only. The 6 litre model comprises 2 x 3L tanks. Costs 8 p a day for 2 x 3L tanks.



** Sapphire Undersink Chiller specifications see page 26

Boiling Specification

Outer Casing

Tap-polished chrome finish as standard
Other tap finishes available at additional cost (page 13)
Tank-durable high impact PC/ ABS

Water Tank

High quality grade 316L stainless steel

Heating Element

Incoloy

Thermostat

Electronic to control water up to boiling point

Insulation

Highly efficient aerogel thermal insulation

Initial Draw off

16 cups/ 11 mugs based on 167 ml cup and 250 ml mug.
Double draw off for 6 litre model.

Safety

Overheat temperature protection (manual re-set).

Safety lock mechanism.

Supplied expansion vessel and pressure relief valve must be fitted.

IP Rating

IPX1

Installation

This appliance must be installed in a frost free environment.
Required hole diameter for mounting tap 32mm – fits in a standard sink.
Sink/counter top up to 50mm thick.

Plumbing

Must be installed by a suitably qualified person.

Intended for connection to the mains water supply.

Minimum water pressure 1 bar.
Maximum water pressure 4.2 bar.
If higher than this a pressure reducing valve may be required.

Supplied filter, expansion vessel and pressure relief valve must be fitted.

Electrical Connection

Installation must comply with current IEE wiring regulations.

Supplied with a pre-wired (1m) BS plug.

Approvals

CE, WRAS (98°C model only)

Standard Warranty

2 years parts or replacement warranty. Supplied scale filter must be fitted and changed at least every 6 months otherwise the warranty may be void.

Product Code	Height (mm)	Width (mm)	Depth (mm)	Weight (kg)	
				Empty	Full
ZEN Spa Tap	320	224	56	1.1	–
ZEN Tank 3L	460	182	221	5.8	8.8
ZEN Tank 6L	460	230	270	6.7	12..7